

LD PUMPEDALL-SOLID-STATEUV LASER

MP_

RN-N-257/0.1~4uJ/1~15mW

产品描述

All solid state 257 nm UV laser is made features of ultra compact, long lifetime, cost -effectiveness and easy operating, which is widely used in UV curing, micro-electronics, CD carving, laser medical treatment, scientific experiment, etc.

产品参数

RN-N-257/0.1~4uJ/1~15mW	
Central wavelength (nm)	257±1
Output average power (mW)	1~15
Transverse mode	Near TEM00, elliptical
Operating mode	Pulsed, Cr : YAG passively Q-switched
Single pulse energy (µJ)	0.1~4
Pulse duration (ns)	~10
Peak power (W)	~400
Rep. rate (kHz)	QCW state with one rep. rate between 2kHz-5kHz
Average power (mW)	Average power (mW) = Single pulse energy (µJ) * Rep. rate (kHz)
Ave power stability (over 4 hours)	<10%
Beam parameters	Elliptical (4:1), Beam spot 0.5*2mm
Warm-up time (minutes)	<10
Beam height from base plate (mm	70
Operating temperature ($^{\circ}\!$	10~35
Power supply (90-264VAC)	PSU-H-FDA
Cooling system	Air
Expected lifetime (hours)	5000
Warranty period	1 year
Remarks	Please Note: because of the Walk-off effect of
	Nonlinear crystals, the beam quality of UV laser is
	not so good as that of 1064/532nm laser.

