

## LD PUMPED ALL-SOLID-STATE UV LASER

RN-F-266/0.1~3uJ/1~10mW

### 产品描述



All solid state 266 nm UV laser is made features of ultra compact, long lifetime, cost -effectiveness and easy operating, which is widely used in UV curing, micro-electronics, CD carving, laser medical treatment, scientific experiment, etc

### 产品参数

RN-F-266/0.1~3uJ/1~10mW		
Central wavelength (nm)	266±1	
Output average power (mW)	1~10	
Transverse mode	Near TEM <sub>00</sub>	
Operating mode	Frequency conversion of Q-switched pulsed laser	
Single pulse energy (μJ)	0.1~3	
Pulse duration (ns)	~5	
Peak power(W)	20~600	
Rep. rate (kHz)	FIXED	Setting up one fixed rep. rate internal between 1kHz-4kHz with stable pulse energy,pulse duration and pulse period
	EXT TRIG	1kHz-4kHz by external trigger with stable pulse energy, pulse duration and pulse period.
	QCW	QCW state with one rep. rate between5kHz-7kHz.
Average power (mW)	Average power (mW) = Single pulse energy (μJ) * Rep. rate (kHz)	
Ave power stability (over 4 hours)	<5%, <10%	
Warm-up time (minutes)	<10	
M <sup>2</sup> factor	<1. 5	
Spectral purity	>99%	
Beam parameters	Elliptical (4:1), Beam spot ~2mm	
Polarization ratio	>100:1	
Beam height from base plate (mm)	45	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-H-FDA	
Expected lifetime (hours)	5000	
Warranty period	1 year	
Remarks	Please Note: because of the Walk-off effect of Nonlinear crystals, the beam quality of UV laser is not so good as that of 1064/532nm laser.	

