LD PUMPED ALL-SOLID-STATE CW UV LASER

RN-F-303/1~5mW





All solid state 303nm UV laser is made features of ultra compact, long lifetime, cost

-effectiveness and easy operating, which is used in DNA sequencing, flow cytometry,

cell sorting, optical instrument, spectrum analysis, measurement, physics

experiment, laser rapid modeling, etc.

产品参数

| RN-266-Pico/100~500mW | |
|--|------------------------|
| Wavelength (nm) | 303±1 |
| Operating mode | CW |
| Output power (mW) | >1, 2,, 5 |
| Power stability (rms, over 4 hours) | <10% |
| Transverse mode | Near TEM ₀₀ |
| M ² factor | <2. 0 |
| Beam diameter at the aperture (mm) | ~3. 0 |
| Beam divergence, full angle (mrad) | <2.0 |
| Polarization ratio | >50:1 (Horizontal) |
| Warm-up time (minutes) | <10 |
| Beam height from base plate (mm) | 45 |
| Operating temperature ($^{\circ}\!\!\mathbb{C}$) | 10~35 |
| Spectral purity | >99% |
| Power supply (90-264VAC) | PSU-H-FDA |
| Expected lifetime (hours) | Warranty period |
| Warranty period | 1 year |



北京市昌平区 国家信息产业基地立业路13号2011 ≤ sales@ranbond.com