LD PUMPED ALL-SOLID-STATE CW UV LASER

UV-F-349/1~100mW

产品描述



All solid state 349nm UV laser is made features of ultra compact, long lifetime, cost

-effectivenessand easy operating, which is used in DNA sequencing, flow cytometry,

cell sorting, optical instrument, spectrum analysis, measurement, physics

experiment, laser rapid modeling, etc

产品参数

UV-F-349/1~100mW	
Wavelength (nm)	349±1
Operating mode	CW
Output power (mW)	>1, 2,, 100
Power stability (rms, over 4 hours)	<3%,<5%,<10%
Transverse mode	Near TEM ₀₀
M ² factor	<2.0
Beam diameter at the aperture (mm)	~1.5
Beam divergence, full angle (mrad)	<2.5
Polarization ratio	>50:1 Horizontal +5degree (Vertical Optional)
Warm-up time (minutes)	<10
Beam height from base plate (mm)	45
Operating temperature ($^{\circ}\!\!\mathbb{C}$)	10~35
Spectral purity	>99%
Power supply (90-264VAC)	PSU-H-FDA
Expected lifetime (hours)	5000
Warranty period	1 year

X

北京市昌平区 国家信息产业基地立业路13号2011 ≤ sales@ranbond.com