

LD PUMPED ALL-SOLID-STATE

INFRARED LASER AT 914nm

RN-SU-914/800~1700mW

产品描述

All solid state infrared laser at 914nm is made features of ultra compact, long

lifetime, low cost and easy operating, which is used in scientific experiment, optical

sensor, measurement, instrument, communication, spectrum analysis, etc.

产品参数

RN-SU-914/800~1700mW	
Wavelength (nm)	914±1
Output power (mW)	>800,1000,1700
Power stability (rms, over 4 hours)	<2%, <3%, <5%
Transverse mode	Near TEM ₀₀
Operating mode	CW
Warm-up time (minutes)	<10
M ² factor	<2.0
Beam divergence, full angle (mrad)	<2.0
Beam diameter at the aperture (mm)	~3. 0
Polarization ratio	>100:1 Horizontal±5 degree (Vertical Optional)
Beam height from base plate (mm)	27.4
Pointing stability after warm-up (mrad)	<0.05
Operating temperature ($^\circ\!\!\!\mathrm{C}$)	10~35
Power supply (90-264VAC or 5VDC)	PSU-H-LED /PSU-H-FDA
Expected lifetime (hours)	10000
Warranty	1 year

北京市昌平区 国家信息产业基地立业路13号2011 ≤ sales@ranbond.com