OEM BLUE DIODE LASER AT 454nm

RN-D-454/7-8W

产品描述

It features ultra compact design, long lifetime, cost-effectiveness and easy operation.

They are widely used in laser projection, stage lighting, biomedical applications,

metrology, etc.



RN-D-454/7-8W	
Central wavelength (nm)	454±5
Operating mode	CW
Output power (mW)	>5000, 6000
Power stability (rms, over 4 hours) at $25^\circ\!\!\mathbb{C}$	<1%, <2%, <3%
Polarization direction	Horizontal+ Vertical
Beam diameter at the aperture (1/e²,mm)	~3.2×3.2
Beam divergence, full angle (mrad)	1.4×0.2
Warm-up time (minutes)	<5
Beam height from base plate (mm)	35
Operating temperature ($^{\circ}\!\!\!\mathrm{C}$)	25+/-3
Driver (12VDC 15A)	PSU-6R-OEM/ PSU-6R-OEM-H
TTL / Analog modulation	TTL or Analog with 1Hz-1kHz 1kHz-10kHz, 10kHz-30kHz optional
Expected lifetime (hours)	10000
Warranty	1 year

北京市昌平区 国家信息产业基地立业路13号2011 云 sales@yanbanlaser.com

010-57513647