YANBAN LASER

FREQUENCY STABILIZED SLM LASER

RN-FN-660-S/1-20mW

产品描述

Single longitudinal mode, frequency stabilized laser is made features of stable frequency and low frequency noise, which is used in optical frequency standards, gravitational wave detection, tests of fundamental physics, atomic clocks, high resolution spectrum, Laser Radar, precision measurement, etc.

产品参数

| RN-FN-660-S/1-20mW | |
|---|-------------------|
| Wavelength (nm) | 660±1 |
| Operating mode | CW |
| Output power (mW) | >1, 2, 3,, 20 |
| Power stability (rms, over 4 hours) | <3%, <5% |
| Transverse mode | TEM ₀₀ |
| Longitudinal mode | Single |
| Spectral linewidth (nm) | <0.00001 |
| Noise of amplitude (rms, 1Hz~20MHz) | <1%, typical<0.5% |
| Beam diameter at the aperture (1/e²,mm) | <2.0 |
| Beam divergence, full angle (mrad) | <1.2 |
| Warm-up time (minutes) | <10 |
| Pointing stability after warm-up (mrad) | <0.05 |
| Frequency shift over 8 hours (MHz) | <±200 |
| Frequency shift with Temp (MHz/℃) | <200 |
| Coherent length (m) | >50 |
| M ² factor | <1.2 |
| Extra heatsink | TC-01 |
| Expected lifetime (hours) | 10000 |
| Warranty | 1 year |



北京市昌平区 国家信息产业基地立业路13号2011 Mailes@yanbanlaser.com