## LD PUMPED ALL-SOLID-STATE UV LASER

MPL-Q1-266/10uJ/10mW



NG



All solid state 266 nm UV laser is made features of ultra compact, long lifetime,

cost -effectiveness and easy operating, which is widely used in UV curing,

micro-electronics, CD carving, laser medical treatment, scientific experiment,

etc.



MPL-Q1-266/10uJ/10mW	
Wavelength (nm)	266±1
Operating mode	Frequency conversion of Q-switched pulsed laser
Max average power (mW)	~10
Single pulse energy (µJ)	~10
Pulse duration (ns)	~10
Peak power(kW)	~10
Rep. rate (kHz)	1kHz
Average power (mW)	Average power (mW) = Single pulse energy (μJ) * Rep. rate (kHz)
Ave power stability (over 4 hours)	<5%, <10%
Transverse mode	Near TEM <sub>00</sub> ,Elliptical
Beam diameter at the aperture(mm)	<1.2mm
Warm-up time (minutes)	<10
Beam height from base plate (mm)	35
Operating temperature ( $^\circ\!\mathbb{C}$ )	10~35
Power supply (90-264VAC)	PSU-H-LED/PSU-H-FDA
Expected lifetime (hours)	5000
Warranty period	1 year
Remarks	Please Note: because of the Walk-off effect of Nonlinear crystals, the
	beam quality of UV laser is not so good as that of 1064/532nm laser.

北京市昌平区 国家信息产业基地立业路13号2011 ≤ sales@ranbond.com