

## BLUE DIODE LASER AT 454nm

RN-III-454L/1~80mW

### 产品描述

It features ultra compact design, long lifetime, cost-effectiveness and easy operation.

They are used in scientific research, measurement, communication, spectrum analysis, etc.

### 产品参数

RN-III-454L/1~80mW		
Central wavelength(nm)	454±5	
Operating mode	CW	
Output power(mW)	>1, 10, 20, ..., 80	
Power stability(rms, over 4 hours)	<1%, <2%, <3% (<0.5%, optional)	
Transverse mode	Near TEM <sub>00</sub>	
M-factor	<1.5	
Beam diameter at the aperture(1/e <sup>2</sup> mm)	~3.5	
Beam divergence,full angle(mrad)	<1.0	
Polarization ratio	>50:1(>100:1,optional) Horizontal±5 degree(Vertical Optional)	
Warm-uptime(minutes)	<5	
Pointing stability after warm-up (mrad)	<0.05	
Beam height from base plate(mm)	24.8	
Operating temperature(°C)	10~35	
Power supply	85-264VAC	PSU-III-LED/ PSU-III-FDA (Frequency for 1Hz-30kHz)
	100-240VAC	PSU-A-D (Frequency for 30kHz -100kHz)
TTL / Analog modulation	TTL or Analog with 1Hz-1kHz 1kHz-10kHz, 10kHz-30kHz, 30kHz-100kHz optional	
Expected lifetime(hours)	10000	
Warranty	1 year	