

RN SERIES LASER AT 470nm

RN-III-470/1~800mW

产品描述

It features ultra compact design, long lifetime, cost-effectiveness and easy operation. They are widely used in laser projection, stage lighting, biomedical applications, metrology, etc.

产品参数

RN-III-470/1~800mW		
Central wavelength(nm)	470±10	
Operating mode	CW	
Output power(mW)	>1,100,200,...,800	
Power stability(rms, over 4 hours)	<1%, <2%, <3% (<0.5%, optional)	
Transverse mode	Multimode	
Beam diameter at the aperture($1/e^2$ mm)	<3.5×3.0	
Beam divergence,full angle(mrad)	<2.5×0.5	
Warm-up time(minutes)	<5	
Beam height from base plate (mm)	24.8	
Operating temperature (°C)	10~35	
Power supply	85-264VAC	PSU-III-LED/ PSU-III-FDA (Frequency for 1Hz-30kHz)
	100-240VAC	PSU-A-D (Frequency for 30kHz -100kHz)
Modulation	DMOD (TTL) or AMOD (Analog) up to 1MHz	
	DMOD+ AMOD (TTL + Analog)	
TTL / Analog modulation	TTL or Analog with 1Hz-1kHz 1kHz-10kHz, 10kHz-30kHz, 30kHz-100kHz optional	
Expected lifetime(hours)	10000	
Warranty	1 year	