## YANBAN LASER

## LD PUMPED ALL-SOLID-STATE YELLOW LASER

## RN-U-577/1-600mW

## 产品描述

All solid state 577nm yellow laser is made features of ultra compact, long lifetime, cost -effectiveness and easy operating, which is widely used in collimation, laser medical treatment, scientific experiment, optical instrument, laser display, laser lighting show, etc.



| RN-U-577/1~600mW                                 |  |             |
|--|--|-------------|
| Central wavelength (nm)                          | 577±2  |             |
| Operating mode                                   | CW   |             |
| Output power (mW)                                | >10, 20, 50,, 300                              | >300,, 600  |
| Power stability (rms, over 4 hours)              | <1%, <2%,<3%                                   | <2%,<3%,<5% |
| Transverse mode                                  | TEM <sub>00</sub>                              | Multimode   |
| M <sup>2</sup> factor                            | <1.5   | <3          |
| Beam diameter at the aperture(1/e²mm)            | ~3.0   |             |
| Beam divergence,full angle(mrad)                 | <1.5   |             |
| Beam height from base plate (mm)                 | 45   |             |
| Polarization ratio                               | >100:1 Horizontal±5 degree (Vertical Optional) |             |
| Warm-up time (minutes)                           | <10  |             |
| Pointing stability after warm-up (mrad)          | <0.05  |             |
| Operating temperature ( $^\circ\!\!\mathbb{C}$ ) | 10~35  |             |
| Power supply (90-264VAC)                         | PSU-H-LED/PSU-H-FDA/PSU-SR                     |             |
| Modulation option                                | TTL on/off, 1Hz-1KHz                           |             |
| Expected lifetime (hours)                        | 10000  |             |
| Warranty period                                  | 1 year   |             |