YANBAN LASER

## LD PUMPED ALL-SOLID-STATE RED LASER AT 613nm

RN-FN-613/1~20mW

## 产品描述

All solid state 613nm red laser is made features of ultra compact, long lifetime, low

cost and easy operating, which is widely used in measurement, spectrum analysis,

and laser lighting show etc.



| RN-FN-613/1~20mW                         |  |
|--|--|
| Central wavelength (nm)                  | 613±1  |
| Operating mode                           | CW   |
| Output power (mW)                        | >1,5,10,20                                     |
| Power stability (rms, over 4 hours)      | <2%,<3%,<5%                                    |
| Transverse mode                          | Near TEM00                                     |
| M <sup>2</sup> factor                    | <1.2   |
| Beam diameter at the aperture (1/e2, mm) | <1.0   |
| Beam divergence, full angle (mrad)       | <1.5   |
| Polarization ratio                       | >100:1 Horizontal±5 degree (Vertical Optional) |
| Warm-up time (minutes)                   | <10  |
| Pointing stability after warm-up (mrad)  | <0.05  |
| Beam height from base plate (mm)         | 27.4   |
| Operating temperature ( $^{\circ}$ C)    | 10~35  |
| Power supply (90-264VAC)                 | PSU-H-LED/PSU-H-FDA                            |
| Expected lifetime (hours)                | 10000  |
| Warranty                                 | 1 year   |

北京市昌平区