

LD PUMPED ALL-SOLID-STATE

INFRAFED LASER AT 914 nm

RN-III-914/1~400mW

产品描述

All solid state infrared laser at 912nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in scientific experiment, optical instrument, optical sensor, measurement, communication, spectrum analysis, etc.

产品参数

RN-III-914/1~400mW		
Wavelength (nm)	914±1	
Output power (mW)	>1, 10, 20, 30,... , 200	>200, ..., 400
Power stability (rms, over 4 hours)	<1%, <2%, <3%, <5%	<2%, <3%, <5%
Transverse mode	TEM ₀₀	
Operating mode	CW	
Warm-up time (minutes)	<10	
M ² factor	<1.2	
Beam divergence, full angle (mrad)	<1.5	
Beam diameter at (1/e ² ,mm)	~1.5	
Beam height from base plate (mm)	24.8	
Polarization ratio	>100:1 (0 or 90 degree)	
Pointing stability after warm-up (mrad)	<0.05	
Operating temperature (°C)	10~35	
Power supply (90-264VAC or 5VDC)	PSU-III-LED/PSU-III-FDA/PSU-III-OEM-97	
Expected lifetime (hours)	10000	
Warranty period	1 year	