

DIODE XS SERIES LASER AT 915nm

RN-XS-915/1~100mW

产品描述

It features integrated electronics, plug and play, miniaturization, international standard interface. They are the ideal solution for a wide range of applications including life sciences, environmental monitoring, inspection and machine vision.

产品参数

| RN-XS-915/1~100mW | |
|--|--|
| Central wavelength (nm) | 915±5 |
| Operating mode | CW |
| Output power (mW) | >1, 10, 20, ...,100 |
| Power stability (rms, over 4 hours) | <1%, <2%, <3% |
| Transverse mode | Near TEM ₀₀ |
| Noise of amplitude(rms,20Hz~20MHz) | <1%(<0.5%, optional) |
| M ² factor | ~1.5 |
| Beam diameter at the aperture (1/e ² ,mm) | ~1.2 |
| Beam divergence, full angle (mrad) | <1.0 |
| Warm-up time (minutes) | <5 |
| Beam height from base plate (mm) | 19 |
| Operating temperature (°C) | 10~35 |
| Operating voltage | DC12V 4A |
| Modulation | DMOD (TTL) up to 1MHz AMOD (Analog) up to 100kHz DMOD+ AMOD (TTL + Analog) |
| Expected lifetime (hours) | 10000 |
| Warranty period | 1 year |