

LD PUMPED ALL-SOLID-STATE INFRARED LASER AT 1413nm

RN-III-1444/1~400mW

产品描述

All solid state infrared laser is made features of ultra compact, long lifetime, low cost and easy operating, which is used in scientific experiment, optical instrument, optical sensor, measurement, communication, spectrum analysis, etc.

产品参数

RN-III-1444/1~400mW		
Wavelength (nm)	1413±2	
Output power (mW)	>1, 5, 10, 20, ... , 200	>200, ... , 400
Transverse mode	Near TEM ₀₀	
Operating mode	CW	
Power stability (rms, over 4 hours)	<2%, <3%, <5%	<3%, <5%
Warm-up time (minutes)	<10	
M ² factor	<1.5	
Beam divergence, full angle (mrad)	<1.5	
Beam diameter at the 1/e ² (mm)	~1.5	
Beam height from base plate (mm)	24.8	
Pointing stability after warm-up (mrad)	<0.05	
Operating temperature (°C)	10~35	
Power supply (90-264VAC or 5VDC)	PSU-III-LED/PSU-III-FDA/PSU-III-OEM-97	
Modulation option	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option	
Expected lifetime (hours)	10000	
Warranty period	1 year	